

CUT THROUGH ISLAND DETAILS

Check box that applies	CT Type #	CT Island Type	Island Length A	Island Opening Width B		Narning Surface cated Domes)	Roadway Slope C	Counter Slope D	Running Slope E	Cross Slope F	Level / Clear / Turning Space Rect. Area	Level / Clear / Turning Space Slope	Is the Opening Lip Flush?	СТ Туре #
	1	Short Straight (A < 6')	ft											1
a	2	Short Staggered (A < 6')	ft		N/A						N/A	N/A		2
	3	Straight (A ≥ 6')	ft	ft 5'≤B≤9'? Y □ N □	Installed at opening? Y D N D Approved Contrasting Color?	2.0' min. in direction of travel? Y	ft >2.1%? □ ≤2.1%? □	% ≤5.0% ? Y □ N □	% ≤2.1% ? Y ⊡ N □	% ≤ z* ? Y □ N □			Y N	3
	4	Staggered	ft								ft x ft 5' X 5' min. throughout travel way? Y □ N □	≤ 2.1% in all directions within clear space ? Y □ N □		4
	5	Staggered "L"	≥ 10' ? Y □ N □											5
0	6	Corner	N/A		Υ□Ν□	edges? Y □ N □								6

COMMENTS AND IMAGES

RULES FOR MEASURING:	Inspected by:
 Follow level manufacturer's calibration instructions. Level must be an ODOT approved Smart Level. 	
 Provide completed report to Project Engineer for review. 	
	(Inspector C

•

(Print Name)

(Signature) / Date

(Inspector Certification #) Check if ADA Design Variance applies Note: If Design Variance has been approved, attach it.